



Mobil Diesel Special 20W50

Mobil Commercial Vehicle Lube , Pakistan

Multigrade Diesel Engine Oil

Product Description

Mobil Diesel Special 20W-50 is a multigrade diesel engine oil formulated with an optimised combination of base oils and a balanced additive system.

Features and Benefits

| Features | Advantages and Potential Benefits |
|--|---|
| Good protection against rust and corrosion | Longer equipment life and reduced operating costs |
| Thermal and oxidation stability | Controls sludge build-up and deposits |

Applications

- Diesel and gasoline powered equipment where API CD/SF level performance is required
- On-highway light and medium duty trucking
- Off-highway industries including: construction, quarrying, and agriculture

Specifications and Approvals

| | |
|---|--|
| Mobil Diesel Special 20W-50 is recommended by ExxonMobil for use in applications requiring | |
| API CD/SF | |

Typical Properties

| Mobil Diesel Special 20W-50 | |
|--------------------------------------|------|
| Viscosity, ASTM D 445 | |
| cSt @ 40° C | 167 |
| cSt @ 100°C | 18.7 |
| Viscosity Index, ASTM D 2270 | 127 |
| Sulfated Ash, wt%, ASTM D 874 | 0.9 |
| Total Base # , mg KOH/g, ASTM D 2896 | 7 |
| Pour Point, °C, ASTM D 97 | -24 |
| Flash Point, °C, ASTM D 92 | 244 |

| | |
|------------------------------------|-------|
| Mobil Diesel Special 20W-50 | |
| Density @ 15°C kg/l, ASTM D 4052 | 0.882 |

Health and Safety

Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS's are available upon request through your sales contract office, or via the Internet. This product should not be used for purposes other than its intended use. If disposing of used product, take care to protect the environment. The Mobil logotype, the Pegasus and Mobil Super are trademarks of Exxon Mobil Corporation, or one of its subsidiaries.

05-2020

Mobil Askari Lubricants Limited

D-46, Block-5

KDA Scheme-5, Clifton

Karachi, Pakistan

Phone: (92-21) 111-840-840 Fax : (92-21) 583-1013 and 583-0082

<http://www.exxonmobil.com>

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

ExxonMobil

Exxon Mobil Esso

© Copyright 2003-2026 Exxon Mobil Corporation. All Rights Reserved