



Mobil Delvac Modern™ 15W-40 Super Defense

Mobil Commercial Vehicle Lube , Pakistan

Product Description

Mobil Delvac Modern 15W-40 Super Defense is an extra high performance diesel engine oil that provides excellent lubrication of today's diesel engines promoting long engine life. As a result, this product meets or exceeds the specifications of major European and American engine manufacturers. It is recommended by ExxonMobil for use in a wide variety of industries, applications, and mixed fleets.

This product provides outstanding performance in both modern, demanding low-emission diesel engines and older diesel engines operating on low or high sulphur fuel. Mobil Delvac Modern 15W-40 Super Defense is also biodiesel compatible*, it combines a blend of high performance base stocks with a progressive additive system to provide superior control of oil thickening due to soot build-up and high temperatures as well as outstanding resistance to oxidation, corrosion, and high temperature deposits.

This product is fully compatible with Mobil Delvac MX 15w-40 and can be used as a replacement of same

*based on CEC L-109-14 (test modified with palm B100), meeting the limits in ACEA E7-22.

Features and Benefits

High output, low emission diesel engines significantly increase the demands on engine lubricants. Tighter engine designs reduce oil consumption, resulting in less fresh oil make-up to replenish depleted additives. Top piston fire rings are located higher on the piston bringing the oil film closer to the combustion chamber where higher temperatures increase thermal stress on the lubricant. Increased fuel injector pressure and retarded timing improve fuel burn efficiency, but also increase engine temperatures and increase soot loads. Mobil Delvac Modern 15W-40 Super Defense is formulated from high performance base oils and a balanced additive system to provide optimum engine performance in modern diesel and gasoline engines as well as older models. The key benefits include:

Features	Advantages and Potential Benefits
High thermal and oxidation stability	Reduced sludge build-up, deposits and viscosity increase
TBN reserves	Deposit control and acid neutralisation
Stay-in-grade shear stability	Wear protection and viscosity control
High detergency/dispersancy	Clean engines and long component life
Improved soot handling	Improved viscosity control and used oil pumpability
Excellent low temperature properties	Start-up wear protection
Component compatibility	Long gasket and seal life
Meets demanding specifications of key OEMs	One engine oil for mixed fleet operations

Applications

Recommended by ExxonMobil for use in:

- Naturally aspirated and turbo-charged diesel powered equipment from leading Japanese, European, and American manufacturers.

- On-highway light and heavy-duty trucking.
- Off-highway industries including: construction, mining, quarrying, and agriculture.
- Mixed fleet applications.

Specifications and Approvals

This product has the following approvals:
Detroit Fluids Specification 93K215
Mack EO-M Plus
Mack EO-N
RENAULT TRUCKS RLD-2
VOLVO VDS-3
Cummins CES 20077
Cummins CES 20078
DTFR 15B110
MTU Oil Category 2

This product is recommended for use in applications requiring:
API CF
API CF-4
API CG-4
Cummins CES 20071
Cummins CES 20072
Mack EO-M
RENAULT TRUCKS RLD
VOLVO VDS-2

This product meets or exceeds the requirements of:
API CH-4
API CI-4

This product meets or exceeds the requirements of:
API SJ
API SL
JASO DH-1
Caterpillar ECF-2
ACEA E7
Cummins CES 20076
ISUZU DEO (w/o DPD Equipped Vehicles)
ISUZU Small Manual Transmission Oil (except MUA and MUX) and Transfer Case Oil
Ford WSS-M2C171-D

Properties and Specifications

Property	
Grade	SAE 15W-40
Ash, Sulfated, mass%, ASTM D874	1.3
Flash Point, Cleveland Open Cup, °C, ASTM D92	223
Pour Point, °C, ASTM D97	-33
Kinematic Viscosity @ 40 C, mm ² /s, ASTM D445	109
Kinematic Viscosity @ 100 C, mm ² /s, ASTM D445	14.3
Total Base Number, mgKOH/g, ASTM D2896	11
Density @ 15 C, kg/m ³ , ASTM D4052	0.87
Viscosity Index, ASTM D2270	133

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

04-2025

Mobil Askari Lubricants Limited

D-46, Block-5

KDA Scheme-5, Clifton


Karachi, Pakistan

Phone: (92-21) 111-840-840 Fax : (92-21) 583-1013 and 583-0082

<http://www.exxonmobil.com>

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

The ExxonMobil logo, featuring the word "ExxonMobil" in a bold, sans-serif font.The logos for Exxon, Mobil, and Esso, arranged horizontally. Exxon is on the left, Mobil is in the middle, and Esso is on the right.

© Copyright 2003-2026 Exxon Mobil Corporation. All Rights Reserved